

## **AMENDMENTS TO THE CLAIMS**

Claims 1-26 are pending. Please amend claims 2-21 and 23-26. No claims are canceled, added, or withdrawn. The following listing of claims replaces all prior versions and listings of claims in the application.

**1.** (Original) A method for modeling image attention, the method comprising:

preprocessing an image to generate a quantized set of image blocks;  
and

generating a contrast-based saliency map for modeling one-to-three levels of image attention from the quantized image blocks.

**2.** (Currently amended) A The method as ~~recited in~~ of claim 1, wherein preprocessing further comprises:

resizing the image such that an aspect ratio of the image is maintained;

transforming the image from a first color space to a second color space that is consistent with human perception; and

making color in texture areas of the image coarser.

**3.** (Currently amended) A The method as ~~recited in~~ of claim 1, wherein generating the contrast-based saliency map further comprises:

dividing the image subsequent to quantization into multiple perception units; and

calculating a respective contrast of color components for each perception unit; and

normalizing calculated contrasts to smooth the contrasts.

4. (Currently amended) A ~~The method as recited in~~ of claim 1, further comprising extracting attended points from the contrast-based saliency map.

5. (Currently amended) A ~~The method as recited in~~ of claim 1, further comprising extracting an attended area from the contrast-based saliency map.

6. (Currently amended) A ~~The method as recited in~~ of claim 1, further comprising extracting an attended view from the contrast-based saliency map.

7. (Currently amended) A computer-readable medium storing ~~comprising~~ computer-program instructions executable by a processor for modeling image attention, the computer-program instructions when executed by the processor performing operations comprising:

preprocessing an image to generate a quantized set of image blocks;  
and

generating a contrast-based saliency map for three-level contrast-based image attention analysis from the quantized image blocks.

8. (Currently amended) A computer-readable medium storing ~~comprising~~ computer-program instructions ~~for modeling image attention,~~ the computer-program instructions being executable by a processor, the computer-program instructions when executed by the processor for modeling image attention by operations comprising:

generating a preprocessed image by:

resizing the image such that an aspect ratio of the image is maintained; and

if the image is not already in a color space that is consistent with human perception, transforming the image from a first color space to a second color space that is consistent with human perception;

quantizing the preprocessed image to generate quantized image perception units such that color in texture areas across the quantized image perception units are coarser ~~and normalized~~ as compared to the image; and

generating a contrast-based saliency map from the quantized image blocks, the contrast-based saliency map comprising a respective contrast of color components for each perception unit.

9. (Currently amended) A The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for extracting attended points from the contrast-based saliency map.

**10.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for extracting an attended view from the contrast-based saliency map.

**11.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for extracting an attended view from the contrast-based saliency map, the attended view being a rectangle  $V(C, W, H)$ , where  $C$  denotes an attention center, and  $W$  and  $H$  are the width and height of rectangle respectively, the attention center being a centroid of the contrast-based saliency map.

**12.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for determining a size of an attended view in the contrast-based saliency map, the size being related to a 1<sup>st</sup> order central moment of the contrast-based saliency map.

**13.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for extracting an attended area from the contrast-based saliency map.

**14.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for extracting attended areas from the contrast-based saliency map by performing a fuzzy growing operation on the contrast-based saliency map as a function of two classes of pixels to partition the contrast-based saliency map into two mutually exclusive areas, the two classes of pixels comprising attended and unattended pixel areas.

**15.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for:

performing a fuzzy growing operation to extract attended areas from the contrast-based saliency map, the fuzzy growing operation comprising:

partitioning the contrast-based saliency map into two mutually exclusive areas as a function of classes of pixels comprising attended and unattended pixel areas;

selecting seeds to for the fuzzy growing operation according to a set of criteria such that a seed has a local maximum contrast with respect to other regional perception units and the seed belongs to an attended area;

grouping pixels in the contrast-based saliency map with gray levels that satisfy criteria that indicate attended as compared to unattended areas; and

iteratively growing the attended area by using grouped pixel as seeds in subsequent fuzzy growth operations until no candidates of the perception units can be grouped.

**16.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 8, wherein the computer-program instructions further comprise instructions for representing the contrast-based saliency map as a fuzzy event in probability space to extract attended areas.

**17.** (Currently amended) ~~A~~ The computer-readable medium ~~as recited in~~ of claim 16, wherein the contrast-based saliency map 216 has  $L$  gray levels from  $g_0$  to  $g_{L-1}$  and the histogram of saliency map is  $h_k$ ,  $k=0, \dots, L-1$ , and wherein the computer-program instructions further for representing the contrast-based saliency map as a fuzzy event in probability space further comprise instructions for:

modeling the contrast-based saliency map by a triplet  $(\Omega, k, P)$ , where  $\Omega = \{g_0, g_1, \dots, g_{L-1}\}$  and  $P$  is a probability measure of the occurrence of gray levels, i.e.,  $Pr\{g_k\} = h_k / \sum h_k$ ;

denoting a membership function  $\mu_S(g_k)$  of a fuzzy set  $S \in \Omega$  indicating a degree of properties comprising attended areas possessed by gray level  $g_k$ ; and

representing the properties as a fuzzy event as follows:

$$S = \sum_{g_k \in \Omega} \mu_S(g_k) / g_k; \text{ and}$$

computing a probability of the fuzzy event by:

$$P(S) = \sum_{k=0}^{L-1} \mu_S(g_k) P_r(g_k).$$

**18.** (Currently amended) A computing device for modeling image attention, the computing device comprising a processor coupled to a memory, the memory comprising computer computer-program instructions executable by the processor for:

quantizing a preprocessed image to generate quantized image perception units such that color in texture areas across the quantized image perception units are coarser and normalized as compared to the image, the preprocessed image being a resized version of the image with an original aspect ratio and in a color space consistent with human perception; and

generating a contrast-based saliency map from the quantized image blocks, the contrast-based saliency map comprising a respective contrast of color components for each perception unit.

**19.** (Currently amended) ~~A~~ The computing device ~~as recited in~~ of claim 18, wherein the computer-program instructions further comprise instructions for extracting attended points from the contrast-based saliency map.

**20.** (Currently amended) A The computing device ~~as recited in~~ of claim 18, wherein the computer-program instructions further comprise instructions for extracting an attended area from the contrast-based saliency map.

**21.** (Currently amended) A The computing device ~~as recited in~~ of claim 18, wherein the computer-program instructions further comprise instructions for extracting an attended view from the contrast-based saliency map.

**22.** (Original) A computing device comprising:

means for preprocessing an image to generate a quantized set of image blocks; and

means for generating a contrast-based saliency map for modeling three-levels of image attentions from the quantized image blocks.

**23.** (Currently amended) A The computing device ~~as recited in~~ of claim 22, wherein the means for generating the contrast-based saliency map further comprises:

means for dividing the image subsequent to quantization into multiple perception units; and

means for calculating a respective contrast of color components for each perception unit; and

means for normalizing calculated contrasts to smooth the contrasts.



**24.** (Currently amended) A The computing device as ~~recited in~~ of claim 22, further comprising means for extracting attended points from the contrast-based saliency map.

**25.** (Currently amended) A The computing device as ~~recited in~~ of claim 22, further comprising means for extracting an attended area from the contrast-based saliency map.

**26.** (Currently amended) A The computing device as ~~recited in~~ of claim 22, further comprising means for extracting an attended view from the contrast-based saliency map.